



## NEW! 8 Ton Fertilizer Spreader NEW! Row Crop Model - 44 inch Frame Clearance



### Model RC 800 - Features

- 44 inch Frame Clearance
- 40' to 90' Dual Spread Pattern
- Dual Stainless Steel Spinners
- All Hydraulic Drive Standard
- Variable Rate Ready - Hydraulic Drive Only
- Adjustable Row Spacing - 80" to 120"
- Adjustable Hitch Height
- Optional Mechanical Conveyor Drive
- Positive Conveyor Drive
- Split Sprocket Drive From Wheel
- Hydraulically Engage Conveyor from Cab
- Optional PTO 540/1000 Spinner Drive
- Integral Rubber Isolated Lights
- Obstruction Free Interior of Hopper
- Minimal Flat Surfaces
- Hopper & Components 409 Stainless Steel
- Conveyor Chain 304 Stainless Steel
- Frame 6" x 3" x 10 gauge Steel Tubing
- Hitch 1/4" Channel Formed Steel
- 380/90-R46 Tires - 2 Optional Tire Choices
- Integral Hitch & Frame
- Single Bearing Design
- Roll Tarp is Optional



[agspray.com](http://agspray.com)

CALL FOR OPTIONS AND PRICING

FM 3090

## LOFTNESS FERTILIZER SPREADER

Bakersfield, CA  
877.724.2236

Columbus, NE  
800.274.1025

Dothan, AL  
800.227.4098

Fargo, ND  
800.373.4084

Hopkinsville, KY  
800.637.7172


Mankato, MN  
800.722.9376

Newton, KS  
800.394.7662

Pasco, WA  
800.634.2026

Tempe, AZ  
877.974.7166

# Specifications

|                                   |   |  |
|-----------------------------------|---|--|
| Spread Pattern (Dual)(Hydraulic)  | 40-90 ft.   |  |
| Spread Pattern (Dual)(Mechanical) | 50 ft.  |  |
| Hopper Capacity-Struck            | 241 cu. ft.   |  |
| Hopper Capacity-Heaped            | 266 cu. ft.   |  |
| Weight-Empty                      | 4320 lbs.   |  |
| Max Gross Weight                  | 20,000 lbs.   |  |
| Overall Length                    | 206 in.   |  |
| Frame/Crop Clearance              | 44 in.  |  |
| Overall Width                     | 95 -135 in.   |  |
| Overall Height                    | 119 in.   |  |
| Hopper Length                     | 120 in.   |  |
| Hopper Width                      | 92 in.  |  |
| Hopper Height                     | 54 in.  |  |
| Standard Tires                    | 380/90-R46  |  |
| Axles/Suspension                  | 6 x 6 in. - infinitely adjustable from 80 - 120 in.     |  |
| Frame                             | 6 x 3 in. x 10 ga. rectangular tubing                   |  |
| Hitch                             | ¼ in., hot-rolled sheet, channel-formed                 |  |
| Drawbar                           | Bolt-in, adjustable position                            |  |
| Hopper                            | 12-gauge, 409 stainless steel                           |  |
| Skid                              | 12-gauge, 409 stainless steel                           |  |
| Gate                              | 7-gauge, 409 stainless steel                            |  |
| Conveyor Chain                    | 7-in. wide, 304 stainless steel with 1-in. x 1-in. mesh |  |
| Spinner Dish                      | 19" dia. 7 gauge, 409 stainless steel                   |  |

## Options

|                |  |
|----------------|--|
| Conveyor Drive | Hydraulic Drive (Standard)<br>Mechanical Drive (Optional)<br>Two-speed axle-driven transmission<br>Hydraulic engage/disengage from cab<br>Stainless steel chains |
| Spinner Drive  | Hydraulic drive (Standard)<br>540 rpm PTO (Optional)<br>540/1000 rpm dual-drive PTO (Optional)   |
| Tires          | 480/80-R42 or 320/90-R50   |
| Roll Tarp      | Optional   |



[agspray.com](http://agspray.com)