



TeeJet® VisiFlo® Flat Spray Tips

Features:

- Tapered edge flat spray pattern for uniform coverage in broadcast spraying.
- VisiFlo color-coded version available in stainless steel, ceramic and polymer in 80° or 110° spray angles in selected sizes.
- Available in ceramic 80° capacities 01–02 and 110° capacities 01–015. See XR and XRC TeeJet® tips on page 12–13 for larger capacities.
- Standard version (not color-coded) available in 15°, 25°, 40°, 50° and 65° spray angles in brass, stainless steel or hardened stainless steel.
- See page 35 for TeeJet even flat spray tips.
- Automatic spray alignment with 25612-*NYR Quick TeeJet® cap and gasket. Reference page 57 for more information.
- Automatic spray alignment for sizes 10 through 20 with 25610-*NYR Quick TeeJet cap and gasket. Reference page 64 for more information.



	PSI	DROP SIZE 80°/110°	CAPACITY ONE NOZZLE IN GPM	CAPACITY ONE NOZZLE IN OZ./MIN.	20"								GALLONS PER 1000 SQ. FT.				
					4 MPH	5 MPH	6 MPH	8 MPH	10 MPH	12 MPH	15 MPH	20 MPH	2 MPH	3 MPH	4 MPH	5 MPH	
TP650050†	30		0.043	5.5	3.2	2.6	2.1	1.6	1.3	1.1	0.85	0.64	0.15	0.10	0.07	0.06	
TP800050†	35		0.047	6.0	3.5	2.8	2.3	1.7	1.4	1.2	0.93	0.70	0.16	0.11	0.08	0.06	
TP1100050† (100)	40		0.050	6.4	3.7	3.0	2.5	1.9	1.5	1.2	0.99	0.74	0.17	0.11	0.09	0.07	
TP1100050† (100)	50		0.056	7.2	4.2	3.3	2.8	2.1	1.7	1.4	1.1	0.83	0.19	0.13	0.10	0.08	
TP1100050† (100)	60		0.061	7.8	4.5	3.6	3.0	2.3	1.8	1.5	1.2	0.91	0.21	0.14	0.10	0.08	
TP650067†	30		0.058	7.4	4.3	3.4	2.9	2.2	1.7	1.4	1.1	0.86	0.20	0.13	0.10	0.08	
TP800067†	35		0.063	8.1	4.7	3.7	3.1	2.3	1.9	1.6	1.2	0.94	0.21	0.14	0.11	0.09	
TP1100067† (100)	40		0.067	8.6	5.0	4.0	3.3	2.5	2.0	1.7	1.3	0.99	0.23	0.15	0.11	0.09	
TP1100067† (100)	50		0.075	9.6	5.6	4.5	3.7	2.8	2.2	1.9	1.5	1.1	0.26	0.17	0.13	0.10	
TP1100067† (100)	60		0.082	10	6.1	4.9	4.1	3.0	2.4	2.0	1.6	1.2	0.28	0.19	0.14	0.11	
TP6501†	30	F F	0.087	11	6.5	5.2	4.3	3.2	2.6	2.2	1.7	1.3	0.30	0.20	0.15	0.12	
TP8001	35	F F	0.094	12	7.0	5.6	4.7	3.5	2.8	2.3	1.9	1.4	0.32	0.21	0.16	0.13	
TP11001 (100)	40	F F	0.10	13	7.4	5.9	5.0	3.7	3.0	2.5	2.0	1.5	0.34	0.23	0.17	0.14	
TP11001 (100)	50	F F	0.11	14	8.2	6.5	5.4	4.1	3.3	2.7	2.2	1.6	0.37	0.25	0.19	0.15	
TP11001 (100)	60	F VF	0.12	15	8.9	7.1	5.9	4.5	3.6	3.0	2.4	1.8	0.41	0.27	0.20	0.16	
TP65015†	30	F F	0.13	17	9.7	7.7	6.4	4.8	3.9	3.2	2.6	1.9	0.44	0.29	0.22	0.18	
TP80015	35	F F	0.14	18	10.4	8.3	6.9	5.2	4.2	3.5	2.8	2.1	0.48	0.32	0.24	0.19	
TP110015 (100)	40	F F	0.15	19	11.1	8.9	7.4	5.6	4.5	3.7	3.0	2.2	0.51	0.34	0.26	0.20	
TP110015 (100)	50	F F	0.17	22	12.6	10.1	8.4	6.3	5.0	4.2	3.4	2.5	0.58	0.39	0.29	0.23	
TP110015 (100)	60	F F	0.18	23	13.4	10.7	8.9	6.7	5.3	4.5	3.6	2.7	0.61	0.41	0.31	0.24	
TP6502†	30	F F	0.17	22	12.6	10.1	8.4	6.3	5.0	4.2	3.4	2.5	0.58	0.39	0.29	0.23	
TP8002	35	F F	0.19	24	14.1	11.3	9.4	7.1	5.6	4.7	3.8	2.8	0.65	0.43	0.32	0.26	
TP11002 (50)	40	F F	0.20	26	14.9	11.9	9.9	7.4	5.9	5.0	4.0	3.0	0.68	0.45	0.34	0.27	
TP11002 (50)	50	F F	0.22	28	16.3	13.1	10.9	8.2	6.5	5.4	4.4	3.3	0.75	0.50	0.37	0.30	
TP11002 (50)	60	F F	0.24	31	17.8	14.3	11.9	8.9	7.1	5.9	4.8	3.6	0.82	0.54	0.41	0.33	
TP6503†	30	F F	0.26	33	19.3	15.4	12.9	9.7	7.7	6.4	5.1	3.9	0.88	0.59	0.44	0.35	
TP8003	35	F F	0.28	36	21	16.6	13.9	10.4	8.3	6.9	5.5	4.2	0.95	0.63	0.48	0.38	
TP11003 (50)	40	F F	0.30	38	22	17.8	14.9	11.1	8.9	7.4	5.9	4.5	1.0	0.68	0.51	0.41	
TP11003 (50)	50	F F	0.34	44	25	20	16.8	12.6	10.1	8.4	6.7	5.0	1.2	0.77	0.58	0.46	
TP11003 (50)	60	F F	0.37	47	27	22	18.3	13.7	11.0	9.2	7.3	5.5	1.3	0.84	0.63	0.50	
TP6504†	30	M M	0.35	45	26	21	17.3	13.0	10.4	8.7	6.9	5.2	1.2	0.79	0.60	0.48	
TP8004	35	M M	0.37	47	27	22	18.3	13.7	11.0	9.2	7.3	5.5	1.3	0.84	0.63	0.50	
TP11004 (50)	40	M M	0.40	51	30	24	19.8	14.9	11.9	9.9	7.9	5.9	1.4	0.91	0.68	0.54	
TP11004 (50)	50	F F	0.45	58	33	27	22	16.7	13.4	11.1	8.9	6.7	1.5	1.0	0.77	0.61	
TP11004 (50)	60	F F	0.49	63	36	29	24	18.2	14.6	12.1	9.7	7.3	1.7	1.1	0.83	0.67	
TP6505†	30	M M	0.43	55	32	26	21	16.0	12.8	10.6	8.5	6.4	1.5	0.97	0.73	0.58	
TP8005	35	M M	0.47	60	35	28	23	17.4	14.0	11.6	9.3	7.0	1.6	1.1	0.80	0.64	
TP11005 (50)	40	M M	0.50	64	37	30	25	18.6	14.9	12.4	9.9	7.4	1.7	1.1	0.85	0.68	
TP11005 (50)	50	M F	0.56	72	42	33	28	21	16.6	13.9	11.1	8.3	1.9	1.3	0.95	0.76	
TP11005 (50)	60	F F	0.61	78	45	36	30	23	18.1	15.1	12.1	9.1	2.1	1.4	1.0	0.83	
TP6506†	30	M M	0.52	67	39	31	26	19.3	15.4	12.9	10.3	7.7	1.8	1.2	0.88	0.71	
TP8006	35	M M	0.56	72	42	33	28	21	16.6	13.9	11.1	8.3	1.9	1.3	0.95	0.76	
TP11006 (50)	40	M M	0.60	77	45	36	30	22	17.8	14.9	11.9	8.9	2.0	1.4	1.0	0.82	
TP11006 (50)	50	M M	0.67	86	50	40	33	25	19.9	16.6	13.3	9.9	2.3	1.5	1.1	0.91	
TP11006 (50)	60	M F	0.73	93	54	43	36	27	18.1	14.5	10.8	2.5	1.7	1.2	0.99		
TP6508†	30	C C	0.69	88	51	41	34	26	20	17.1	13.7	10.2	2.3	1.6	1.2	0.94	
TP8008	35	C M	0.75	96	56	45	37	28	22	18.6	14.9	11.1	2.6	1.7	1.3	1.0	
TP11008 (50)	40	M M	0.80	102	59	48	40	30	24	19.8	15.8	11.9	2.7	1.8	1.4	1.1	
TP11008 (50)	50	M M	0.89	114	66	53	44	33	26	22	17.6	13.2	3.0	2.0	1.5	1.2	
TP11008 (50)	60	M M	0.98	125	73	58	49	36	29	24	19.4	14.6	3.3	2.2	1.7	1.3	
TP6510†	30	C C	0.87	111	65	52	43	32	26	22	17.2	12.9	3.0	2.0	1.5	1.2	
TP8010†	35	C C	0.94	120	70	56	47	35	28	23	18.6	14.0	3.2	2.1	1.6	1.3	
TP11010†	40	C M	1.00	128	74	59	50	37	30	25	19.8	14.9	3.4	2.3	1.7	1.4	
TP11010†	50	C M	1.12	143	83	67	55	42	33	28	22	16.6	3.8	2.5	1.9	1.5	
TP11010†	60	C M	1.22	156	91	72	60	45	36	30	24	18.1	4.1	2.8	2.1	1.7	
TP6515†	30	VC VC	1.30	166	97	77	64	48	39	32	26	19.3	4.4	2.9	2.2	1.8	
TP8015†	35	VC C	1.40	179	104	83	69	52	42	35	28	21	4.8	3.2	2.4	1.9	
TP11015†	40	VC C	1.50	192	111	89	74	56	45	37	30	22	5.1	3.4	2.6	2.0	
TP11015†	50	C C	1.68	215	125	100	83	62	50	42	33	25	5.7	3.8	2.9	2.3	
TP11015†	60	C C	1.84	236	137	109	91	68	55	46	36	27	6.3	4.2	3.1	2.5	
TP6520†	30		1.73	221	128	103	86	64	51	43	34	26	5.9	3.9	2.9	2.4	
TP8020†	35		1.87	239	139	111	93	69	56	46	37	28	6.4	4.2	3.2	2.5	
TP8020†	40		2.00	256	149	119	99	74	59	50	40	30	6.8	4.5	3.4	2.7	
TP8020†	50		2.24	287	166	133	111	83	67	55	44	33	7.6	5.1	3.8	3.0	
TP8020†	60		2.45	314	182	146	121	91	73	61	49	36	8.3	5.6	4.2	3.3	

Note: Always double check your application rates. Tabulations are based on spraying water at 70°F (21°C). See pages 136–157 for drop size classification, useful formulas and other information.

†Available in brass and/or stainless steel and/or hardened stainless steel.



- How to order:**
Specify tip number.
Examples:
- | | |
|-------------|---|
| TP8002VS | - Stainless Steel with VisiFlo color-coding |
| TP11002VP | - Polymer with VisiFlo color-coding |
| TP11002-HSS | - Hardened Stainless Steel |
| TP8002-SS | - Stainless Steel |
| TP8002 | - Brass |